




In or Out...we make it Easy!®

Features & Benefits



8310-IQ

Single Outswinging
Interior or Perimeter Doors



8310

Single Outswinging
Interior or Perimeter Doors



8320-IQ

Double Outswinging Interior
or Perimeter Doors
without Mullion



8320

Double Outswinging Interior
or Perimeter Doors
without Mullion



8330

With Extended Housing
Maximum Length 34 1/2"/876mm



8340

With Extended Housing
Maximum Length 46 1/2"/1181mm



8360

Mortise Mount
For Sliding Doors



8365

Mortise Mount For Sliding
Doors or Drawers

8310 Multimag® and 8310-IQ Intellimag® 8320 Multimag® and 8320-IQ Intellimag® 8330 Multimag® 8340 Multimag®

- Brushed Anodized Aluminum or Brushed Dark Bronze finish
- Adjustable keyhole mounting bracket
- Built-in time delay (instant release with adjustable relock, programmable from 0 -110 secs.)
- Field Selectable – 12/24VDC
- Convenient plug-in wiring terminals
- Easy-access wiring cavity
- Stabilizing 4 bolt "Drop Stop" mounting
- MOV surge protection
- No residual magnetism
- Low energy consumption
- Hardened steel armature nut
- Self-drilling tek™ fasteners
- Lock Status Sensor (LSS x LED)
- Optional DSS feature door status sensor
- Optional SCS feature security condition sensor
- Length modifications on site after cutting, using special endcaps (minimum length 24") only available in 8330 and 8340 models
- Alarm Time Setting (only available in 8310-IQ and 8320-IQ Intellimag®)
- Illegal Armature Plate Alarm (only available in 8310-IQ and 8320-IQ Intellimag®)
- Life Time Warranty

8360 Minimag® and 8365 Micromag™

- Low energy consumption
- Field Selectable – 12/24VDC
- MOV surge protection
- Hardened steel armature nut
- Built-in RLS (Remote Lock Status 8360 only)
- Brushed Anodized Aluminum or Brushed Dark Bronze finish
- Life Time Warranty



In or Out...we make it Easy!®

Features & Benefits



8371

Single Outswinging
Interior Doors



8372

Double Outswinging
Interior Doors
without Mullion



8375

Surface Mount For Small
Enclosures and
Outswinging Doors



8380

Single or Double, Swinging
or Sliding, Exterior
or Interior Gates

8371 Minimag® and 8372 Minimag®

- Low energy consumption
- Field Selectable – 12/24VDC
- Stabilizing 4 bolt "Drop Stop" mounting
- Adjustable mounting bracket
- MOV surge protection
- No residual magnetism
- Easy-access wiring cavity
- Hardened steel armature nut
- Brushed Anodized Aluminum or Brushed Dark Bronze finish also available
- Life Time Warranty

8375 Micromag™

- Low profile design
- Low energy consumption
- Field Selectable – 12/24VDC
- MOV surge protection
- Hardened steel armature nut
- Brushed Anodized Aluminum finish also available
- Life Time Warranty

8380 Gatemag®

- No residual magnetism
- Weather-resistant
- Stainless steel housing
- Versatile face or bottom mounting
- Built-in remote lock status (RLS)
- Field-selectable voltage 12/24VDC
- Throughbolt mounting
- 6-1/2' (1.9meters) wire cable
- Up to 1500 lbs. (680 kg.) holding force
- Conduit fitting inside diameter 1/2"
- Conduit fitting outside diameter 3/4"
- MOV surge protection
- Low energy consumption
- Life Time Warranty

