

TouchONE® Door Access

CFS-100
Fingerprint Deadbolt

CFS-100 Fingerprint Deadbolt

CFS-100 Gold



Main Features

- High Performance & Durable Optical Sensor
- Powered by 1.5V x 4 AA Alkaline Batteries
- User Capacity: 99 Fingerprints
- Enrollment / Verification Time: Less than 1 second
- Dual Security Function: Passcode and Fingerprint
- Buzzer and LED Indicators
- Automatic Locking
- Forced Open / Closed Mode
- Material: Zinc Alloy Die-casting except for the battery cover
- Non-Handed
- Surface Mount Type

Private Access

- Commercial or Residential

CFS-100 Chrome



CFS-100 Silver



TouchONE®
www.CVEamericas.com

Security
and
Convenience


Creative Vision Electronics reserves the right to alter product offers and specification at any time without notice.
Creative Vision Electronics is not responsible for photographic or typographic errors.

CFS-100 Specifications

TouchONE® Door Access

TouchONE® Door Access

CFS-100
Fingerprint Deadbolt



011000000101C111110000111C11000010000001111111010101001100000101011110000111011000010000
10110000100000011111110101010011000001010111000011011000010000110
10011000000101011100001101100001000011
10110000100000011111110101010011000001010111000011011000010000110

CFS-100 Fingerprint Deadbolt

100110000001010111100001110100001000011
100110000001010111100001101100001000011

Specifications



Inner Body



Outer Body

	Item	Description
Mechanical	Material	Zinc Alloy Die-Casting (Outer & Inner Body)
	Dimensions	Inner Body : 2-3/4 (W) x 6-5/16 (H) x 1-7/16 (D) inches
		Outer Body : 3-1/16 (W) x 6-5/16 (H) x 1-1/2 (D) inches
		Hole Diameter: 1-1/4 inch (Unit Covers Existing Standard Deadbolt Bore)
	Door Thickness	1-3/8 ~ 2-3/8 inches
	Net Weight	3.9 lbs
Electrical	Voltage	> DC 3.8V
	Battery	1.5V x 4 AA Size Alkaline Battery
	Battery Life	1 year or Longer (15 uses per day)
Fingerprint Identification System	Sensor Type	Optical Lens (SFM-3020-OP)
	Enrollment Time	Less than 1 second
	Verification Time	Less than 1 second
	FRR	1/30 ~ 1/100
	FAR	1/100,000 ~ 1/1,000,000
	User Capacity	99 Fingerprints
	Initiation Sensor	Infrared Sensor Adapted
Operating Temperature		-4°F ~ 167°F; -20 °C ~ 75°C
Emergency Device (No Battery)		9V Terminal for Battery Backup
Special Features	Visible ID and corresponding Fingerprint	Easy deletion of Individual User / All Users
	Door Open/Closed	Passcode (4~12 Digits) and /or Fingerprint Automatic and Manual Locking
	Buzzer and LED Indicators	Open, Error and Low Battery Warning
	Automatic Locking and Temporary Open status	Set up by Code Command

Security
and
Convenience

TouchONE®

Creative Vision Electronics reserves the right to alter product offers and specification at any time without notice.
Creative Vision Electronics is not responsible for photographic or typographic errors.

CFS-100 Specifications



Creative Vision Electronics, Inc.
630 Two Executive Drive
Fort Lee, NJ 07024
Tel: 201.905.9200 Fax: 201.461.8556
www.CVEamericas.com

TouchONE® Door Access