Modern Mailboxes – 4150

Surface Mounted Installation Instructions

Made of sand-cast aluminum with a durable powder coat finish and a heavy-duty sand-cast brass mail flap, Salsbury 4150 modern mailboxes will provide years of maintenance free service.

Mounting the Modern Mailbox to a Flat Wall


- 1. The installation fasteners are not provided due to the variation in wall types to which the mailbox might be mounted. Select fasteners and anchors appropriate for the type of wall.
- 2. Mounting access is provided by opening the mail flap and mail access door.
- 3. Where possible, it is best to shield the mailbox from direct weather conditions.
- 4. Contact your local U.S.P.S. office for the required height of the mailbox on the wall.
- 5. For convenience and security, the mounting holes are double keyholes. See illustration.
- 6. Holding the mailbox aligned horizontally in the mounting position, mark on the wall the position of the two upper mounting holes in the back wall of the mailbox.
- 7. Install the two top fasteners and hang the mailbox loosely on them.
- 8. Mark on the wall the position of the lower ends of the two lower key-holes.
- 9. Remove the mailbox and install the two lower fasteners.
- 10. Remove the lower fasteners, hang the mailbox on the wall, reinstall the two lower fasteners, and securely tighten all four fasteners.

Cleaning

<u>Interior & Painted Exterior</u> – Using a soft cloth or sponge, clean the interior and painted exterior of the mailbox with liquid soap, detergent, or diluted water-soluble household cleaners. Completely remove residue of any cleaning products with water, and thoroughly dry with a clean cloth or paper towel.

<u>Cast Brass Mail Flap</u> – The mail flap may be cleaned as indicated above. <u>DO NOT</u> use abrasive materials on polished cast brass surfaces.

4150 Modern Mailbox



SALSBURY INDUSTRIES