

THIS SIDE UP FOR LHR DOOR

4700 RIM PANIC RATED EXIT DEVICE STANDARD TEMPLATE (FOR PANIC RATED DEVICES ONLY)

(REV: 01)
DWG NO: T-ED00317

FOLD HERE
CAUTION
DO NOT USE DOOR EDGE!

PLACE THIS SIDE ON FRAME STOP
PLACE THIS SIDE ON DOOR

(2x) METAL: DRILL/TAP FOR 1/4"-20
MACHINE SCREWS.
WOOD: PRE-DRILL 1/8" HOLES.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS
TRIM OR SEXBOLTS: DRILL 5/16" CLEARANCE HOLE
ON PUSH SIDE, 3/8" HOLE ON PULL SIDE
WOOD: PRE DRILL 1/8" HOLES

FOR TRIM DRILL 1/2" CLEARANCE HOLE.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS
WOOD: PRE-DRILL 1/8" HOLES
SEXBOLTS: DRILL 5/16" CLEARANCE HOLE ON PUSH SIDE,
3/8" HOLE ON PULL SIDE.

2 1/2"
[64]

2 7/8"
[73]

Ø OF DEVICE AND STRIKE

3/8"
[10]

1 3/16"
[30]

1 7/16"
[37]

19/32"
[15]

DRILL/TAP FOR 1/4"-20
AND INSTALL SCREW
AFTER FINAL ADJUSTEMENTS.

AFTER EXIT DEVICE IS CUT AND
MOUNTED, INSTALL END CAP
BRACKET CENTERED ON DEVICE Ø

40" [1016]
RECOMMENDED HEIGHT MAY BE
DETERMINED BY DESIGN SPEC'S

29/32"
[23]
ADJUST FOR
BEST FIT

2 1/4"
[57]

FINISHED FLOOR
//////

 HOLE LOCATIONS

PRIMARY DIMENSIONS SHOWN IN INCHES,
DIMENSIONS IN [] ARE MILLIMETERS.

THIS SIDE UP FOR RHR DOOR

